



HE4661

Product Data Sheet

HE4661 is a hexafunctional aromatic polyurethane acrylate oligomer.

Characteristics

HE4661 is a hexafunctional aromatic polyurethane acrylate oligomer. This product has high reactivity and is used in high-strength coatings. It is particularly suitable for mobile phone, computer and other electronic product shells, cosmetic packaging, etc. In addition, it can also be used for wood and metal substrates.

Delivery form

100% active ingredients;

Product parameters

Functional base (theoretical):6

Viscosity (60°C, NDJ rotational viscometer): 1400-4200mPa.s

Color number(Gardner): ≤ 1

Appearance: colorless or yellowish clear liquid

Principal properties

Good adhesion,

High reactivity, good resistance to steel wool;

Good toughness, good wear resistance;

Applications

Plastic varnish, vacuum plating topcoat, metal varnish, wood coating.

Storage guidelines

The resin should be stored indoors in original, unopened, undamaged container in a dry place at storage temperature no more than 30°C. Exposure to direct sunlight should be avoided.

Shelf life

Under above mentioned storage condition, the shelf life of the resin will be 120 days after production.

For more than 120 days, the goods are still owned by ZOHO Company, the company's QC can make the corresponding extension of the shelf life after testing qualified.

Material safety

This product data sheet only applies to the latest version of Material Safety Data Sheet. Any updates to safety-related information that are consistent with legal requirements will only be reflected in the safety data sheet, at the same time the Sheet will be updated and published. Information on current classification and labelling, application and process methods, and more safety-related data can be found in the latest Material Safety Data Sheet.